



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/5

QSW-RA300-Sn60-Sn63-CLP

Revision 0
Revision date 2015-05-07

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	QSW-RA300-Sn60-Sn63-CLP
CAS No.	7439-92-1
EC No.	231-100-4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen);
Description	Soldering.

1.3. Details of the supplier of the safety data sheet

Company	Qualitek Europe Ltd
Address	Unit 9 Apex Court Bassendale Road Bromborough Wirral CH62 3RE
Web	www.qualitek.com
Telephone	+ 44(0)151 334 0888
Fax	+ 44(0)151 334 1408
Email address of the competent person	sales@qualitek-europe.com

1.4. Emergency telephone number

Emergency telephone number	+ 44(0)151 334 0888 9.00 am - 5.00 pm Mon -Fri
----------------------------	---------------------------------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 67/548/EEC	T; R61 Xn; R22-33-62 Symbols: T: Toxic.
Main hazards	Harmful if swallowed. Danger of cumulative effects. May cause harm to the unborn child. Possible risk of impaired fertility.
2.1.2. Classification - EC 1272/2008	Acute Tox. 4: H302+H332; Repr. 1A: H360Fd; STOT RE 2: H373; Aquatic Chronic 2: H411;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger

QSW-RA300-Sn60-Sn63-CLP

Revision 0

Revision date 2015-05-07

2.2. Label elements

Hazard Statement	Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled. Repr. 1A: H360Fd - May damage fertility. Suspected of damaging the unborn child. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P202 - Do not handle until all safety precautions have been read and understood. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P281 - Use personal protective equipment as required.
Precautionary Statement: Response	P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
Precautionary Statement: Disposal	Do not empty into drains; dispose of this material and its container in a safe way.

Further information

	Rosin: Caution: exposure to this material may cause certain sensitive individuals to develop eczema and/or asthma. Sensitised persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Danger of cumulative effects. Lead: Warning! Contains lead.
--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 3: Composition/information on ingredients

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Lead		7439-92-1	231-100-4	01-2119513221-59	35-45%	T; R61 Xn; R22-33-62
Tin		7440-31-5	231-141-8	01-2119486474-28	55-65%	
Modified Rosin		65997-05-9	500-163-2	01-2119964093-37	1 - 5%	T; R48/23

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Lead		7439-92-1	231-100-4	01-2119513221-59	35-45%	Acute Tox. 4: H302+H332; Repr. 1A: H360Fd; STOT RE 2: H373; Aquatic Chronic 2: H411;
Tin		7440-31-5	231-141-8	01-2119486474-28	55-65%	
Modified Rosin		65997-05-9	500-163-2	01-2119964093-37	1 - 5%	Acute Tox. 4: H302+H312; Skin Sens. 1: H317; Resp. Sens. 1: H334; STOT SE 3: H335;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

QSW-RA300-Sn60-Sn63-CLP

Revision 0

Revision date 2015-05-07

4.1. Description of first aid measures

Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.
-----------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---------------------------------------------------------------

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---------------------------------------------------------

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---------------------------------------------------------------

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--------------------------------------------------------------------------------------

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	-------------------------------------------------------------------------

6.3. Methods and material for containment and cleaning up

	Avoid raising dust. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	--------------------------------------------------------------------------------------------------------------------------------------------

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	----------------------------------------------------------------------------

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Modified Rosin	WEL 8-hr limit ppm: WEL 15 min limit ppm:	WEL 8-hr limit mg/m3: 0.05 WEL 15 min limit mg/m3: 0.15
QSW-RA300-Sn60-Sn63-CLP (Lead)	DIR: 82/605 8hTWA mg/m3: 0.15 STEL mg/m3: -	8hTWA ppm: - STEL ppm: - NOT: -

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.

SECTION 9: Physical and chemical properties

QSW-RA300-Sn60-Sn63-CLP

Revision 0

Revision date 2015-05-07

9.1. Information on basic physical and chemical properties

State	Solid
Colour	Grey
Flash point	98 °C
Autoignition temperature	226 °C
Melting point	183 - 190 °C
Solubility	Immiscible in water

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

Lead	Oral Rat LD50: 40mg/gm	Dermal Rabbit LD50: 25mg/gm
QSW-RA300-Sn60-Sn63-CLP	Dermal Rat LD50: >2000	Oral Mouse LD50: >2000

SECTION 12: Ecological information

12.2. Persistence and degradability

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

ADR/RID

The product is not classified as dangerous for carriage.

IMDG

The product is not classified as dangerous for carriage.

IATA

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

This Product is Classified to Regulation 1272/2008/EC(CLP).

SECTION 16: Other information

Other information

Text of risk phrases in Section 3

R22 - Harmful if swallowed.
 R33 - Danger of cumulative effects.
 R42/43 - May cause sensitisation by inhalation and skin contact.
 R61 - May cause harm to the unborn child.
 R62 - Possible risk of impaired fertility.

Text of Hazard Statements in Section 3

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled
 Repr. 1A: H360Fd - May damage fertility. Suspected of damaging the unborn child.
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
 Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
 Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin
 Skin Sens. 1: H317 - May cause an allergic skin reaction.
 Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 STOT SE 3: H335 - May cause respiratory irritation.

QSW-RA300-Sn60-Sn63-CLP

Revision 0

Revision date 2015-05-07

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.